



THATCHER COMPANY MATERIAL SAFETY DATA SHEET

PRODUCT: ALK-55

Page 1 of 3

MSDS Date: November 2, 2004
Emergency Contact: 1-800-424-9300

SECTION I

PRODUCT NAME: ALK-55

DOT SHIPPING INFORMATION: Compound, Cleaning, Liquid, 8,
(Sodium hydroxide) NA 1760,
PG II RQ = 1000 lbs.

SECTION II - HAZARDOUS INGREDIENTS

This material contains no ingredients which are known by Thatcher Company to be hazardous unless listed below.

HAZARDOUS MATERIAL	CAS NUMBER	w/w %	EXPOSURE LIMITS IN AIR
Sodium hydroxide	1310-73-2	30 - 35	PEL/TLV = 2 mg/m ³ TWA

The specific identity of some ingredients may be withheld for confidential business purposes. However, all known potential health effects from exposure to these ingredients are being addressed.

SECTION III - PHYSICAL DATA

BOILING POINT (F): Not determined **DENSITY:** About 1.34

VAPOR PRESSURE (mm Hg): 13 @ 60°C **% VOLATILE, BY VOLUME:** 65%

VAPOR DENSITY (air = 1): N/A **EVAPORATION RATE:** N/A

SOLUBILITY IN WATER: Complete

APPEARANCE AND ODOR: Colorless to straw-colored, slightly turbid liquid with no odor.

SECTION IV - FIRE AND EXPLOSION DATA

FLASH POINT: Nonflammable.

FLAMMABLE LIMITS: Lel: N/A Uel: N/A

EXTINGUISHING MEDIA: Water spray, foam, carbon dioxide or dry chemicals.

SPECIAL FIRE-FIGHTING PROCEDURES:

Protective equipment and self-contained breathing apparatus should be worn.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Avoid direct contact with water; considerable heat is generated, resulting in dangerous boiling and spattering.



THATCHER COMPANY MATERIAL SAFETY DATA SHEET
PRODUCT: ALK-55
Page 2 of 3

SECTION V - REACTIVITY DATA

STABILITY:

Stable

HAZARDOUS POLYMERIZATION:

Will not occur

CONDITIONS OR MATERIALS TO AVOID:

Avoid contact with other chemicals, especially organics, metals, and strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon monoxide gas can form upon contact with food and beverages in an enclosed area.

SECTION VI - HEALTH HAZARD DATA

NFPA HAZARDOUS RATING: Health = 3 Flammability = 0 Reactivity = 1

Carcinogenic Listing:

NTP: No ingredients listed in this section.

IARC MONOGRAPHS: No ingredients listed in this section.

OSHA 29 CFR 1910: No ingredients listed in this section.

ENTRY ROUTES & EFFECTS OF OVEREXPOSURE:

Contact: Corrosive, can cause extensive burns to eyes, skin and mucous membranes. Severe contact can result in permanent blindness.

Inhalation: Vapor can cause discomfort and/or tissue damage to lungs and upper respiratory tract.

Ingestion: Highly toxic. Harmful or fatal if swallowed. Causes severe burns to the gastrointestinal system.

STATEMENT OF PRACTICAL TREATMENT:

Contact: IMMEDIATELY flush exposed area thoroughly with water. For eyes, flush for at least 15 minutes. Obtain prompt medical assistance.

Inhalation: Remove at once to fresh air. If breathing has stopped, administer artificial respiration. Seek medical attention.

Ingestion: If conscious, give several glasses of water or milk followed by citrus juice or dilute vinegar. DO NOT INDUCE VOMITING! Call a physician or local Poison Control Center at once!



THATCHER COMPANY MATERIAL SAFETY DATA SHEET

PRODUCT: ALK-55

Page 3 of 3

SECTION VII - SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS:

Avoid all contact. Do not take internally. Do not breathe vapor. Wash thoroughly after handling. Ensure lids are tightly secured. Store in a cool, dry area.

STEPS TO BE TAKEN IF MATERIAL SPILLS OR LEAKS:

Evacuate area. Wear proper safety equipment. Dike the liquid and recover into containers. Dilute residue with water and neutralize with sodium bicarbonate. Place into containers for proper disposal. (See below).

WASTE DISPOSAL METHOD:

Waste product is an EPA hazardous waste (D002) due to corrosivity and must be disposed of at an EPA approved waste disposal facility. Contact local EPA office. Comply with all local, state and federal regulations.

OTHER PRECAUTIONS:

Avoid contact with aluminum, tin, strong acids, zinc and alloys.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Self-contained organic respirator must be available.

VENTILATION: Maintain ventilation to keep TLV below 2 mg/m³.

EYE PROTECTION: Chemical goggles, face shield.

SKIN PROTECTION: Acid suit, rubber boots, vinyl or neoprene gloves.

OTHER PROTECTIVE EQUIPMENT: As needed to avoid all bodily contact and breathing of vapor.

ACGIH = American Conference of Governmental Industrial Hygienists

CL = Ceiling Level

IARC = International Agency for Research on Cancer: Monographs

OSHA = Occupational Safety and Health Administration

N/A = Not Applicable

NTP = National Toxicology Program: Annual Report on Carcinogens

PEL = Permissible Exposure Level (OSHA)

TLV = Threshold Limit Value (ACGIH)

TWA = Time Weighted Average over 8 Hours

STEL = Short Term Exposure Limit (ACGIH)

ND = Not Determined

This information is, to the best of our knowledge, accurate but may not be complete. THATCHER COMPANY furnishes this information in good faith, but without warranty, representation or guarantee of its accuracy, completeness, or reliability.