



THATCHER COMPANY MATERIAL SAFETY DATA SHEET
PRODUCT: T-FLOC 1465
Page 2 of 3

SECTION V - REACTIVITY DATA

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS OR MATERIALS TO AVOID: Avoid wet and humid conditions. Avoid temperature extremes or ignition sources.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of Carbon and Nitrogen, hydrocarbons and/or ammonia.

SECTION VI - HEALTH HAZARD DATA

Carcinogenic Listing:

NTP: No ingredients listed in this section.

IARC MONOGRAPHS: No ingredients listed in this section.

OSHA 29 CFR 1910: No ingredients listed in this section

ENTRY ROUTES & EFFECTS OF OVEREXPOSURE:

Contact: May cause irritation to the eyes.

Chronic: Contains petroleum distillates. Prolonged repeated exposure to petroleum distillate vapor may cause central nervous system damage as well as heart and blood disorders.

STATEMENT OF PRACTICAL TREATMENT:

Contact: For contact with eyes, flush thoroughly with cool water for at least 15 minutes. If irritation continues, get medical attention.

SECTION VII - SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS:

Keep away from heat, sparks and flames. Use with adequate ventilation. Avoid contact with eyes skin and clothing. Wear impervious gloves when handling. Do not take internally. Wash thoroughly after handling. Keep container closed. Do not use iron, copper or aluminum containers or equipment with product. Store between 10–40°C.

STEPS TO BE TAKEN IF MATERIAL SPILLS OR LEAKS:

Dispose of in accordance with local, state and federal regulations. Product creates an extreme slip hazard. Remove all ignition sources. Dike the area to contain as much spilled material as possible. Remove any remaining material by absorbing with suitable absorbing material and place in a sealed metal container for disposal. Hose spill area well to eliminate slip hazard.

Water spill: The petroleum distillates in this product are classified as an oil under Section 311 of the Clean Water Act. Spills entering (A) surface waters or (B) any water courses or sewers entering or leading to



THATCHER COMPANY MATERIAL SAFETY DATA SHEET
PRODUCT: T-FLOC 1465
Page 3 of 3

surface water that cause a sheen must be reported to the National Response Center at 800-424-8802.

WASTE DISPOSAL METHOD:

Dispose of in a landfill or incinerate in accordance with local, state and federal regulations.

OTHER PRECAUTIONS: None.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Not required in normal use.

VENTILATION: Normal.

EYE PROTECTION: Chemical goggles.

SKIN PROTECTION: Chemical-resistant gloves.

OTHER PROTECTIVE EQUIPMENT: Not required.

ACGIH = American Conference of Governmental Industrial Hygienists

CL = Ceiling Level

IARC = International Agency for Research on Cancer: Monographs

OSHA = Occupational Safety and Health Administration

N/A = Not Applicable

NTP = National Toxicology Program: Annual Report on Carcinogens

PEL = Permissible Exposure Level (OSHA)

TLV = Threshold Limit Value (ACGIH)

TWA = Time Weighted Average over 8 Hours

STEL = Short Term Exposure Limit (ACGIH)

ND = Not Determined

This information is, to the best of our knowledge, accurate but may not be complete. THATCHER COMPANY furnishes this information in good faith, but without warranty, representation or guarantee of its accuracy, completeness, or reliability.